

# QuickScan® QS6500

Linear Imager

## Data Sheet



### Features:

- Aggressive linear imaging performance with up to 15" / 38 cm reading on 100% UPC labels
- Supports RSS and PDF-417 for future industry compatibility
- 2005 Sunrise compliant
- Multi-interface solution supports all popular host terminal interfaces
- Flash memory for easy software upgrades
- Built tough to withstand common POS abuse for many years
- Attractive, yet durable design to complement your point-of-sale



### Mechanical

#### Dimensions

Height: 6.0" / 16.5cm  
 Width: 2.9" / 7.4cm  
 Length: 3.9" / 9.9cm

Weight: 6.4 oz / 181.4 g

### Environmental

#### Temperature Rating

Operating: 32° to 122° F / 0° to 50°C  
 Storage: -40° to 158° F / -40° to 70° C

#### Humidity:

Operating: 5 to 95% NC  
 Storage/Transport: 5 to 95% NC

Vibration: Meets MIL STD-810E

Mechanical Shock: Withstands 50 drops from 5' / 1.5m to concrete

ESD Protection: Functional after multiple 25KV discharges.

Water & Dust: IEC529 Rating IP52DW

### Electrical

Operating Voltage: +4.5 to 14VDC ±5%

Operating Current: 300mA @ 5VDC

Idle Current: 200mA @ 5VDC

### Optical

#### Ambient Light Immunity

Artificial & Sunlight: 86,000 Lux

Light Source: 630nm Visible Red Diode

Scan Rate: 450 scans/sec max

Sensor: 2048 pixel linear imager

Scan Width: 6.3" / 16.5cm @ 7" / 17.8cm from nose

Resolution: 5 mils / .13mm

Print Contrast: 30% or greater

Pitch: ±60°

Skew: ±55°

Depth of Field: Refer to Depth of Field Table below

DEPTH OF FIELD Range Comparisons		
LABEL DENSITY	RANGE*	
	1D MODELS	PDF MODELS
5 mil Linear	2.0 - 5.0" / 51 - 12.7 cm	2.0 - 4.5" / 5 - 11.4 cm
7.5 mils	1.0 - 7.0" / 2.5 - 17.8 cm	1.0 - 6.0" / 2.5 - 16.2 cm
10 mils	0 - 12" / 0 - 30.5 cm	0 - 10.5" / 0 - 26.7 cm
13 mils / 100% UPC	0 - 15" / 0 to 38 cm	0 - 13" / 0 - 33 cm
20 mils	Up to 24" / 61.0 cm	Up to 21" / 53.3 cm
40 mils	Up to 40" / 101.6 cm	Up to 35" / 89 cm

\* Minimum distance determined by symbol length and scan angle. Printing resolution, contrast, and ambient light dependent.

### Decoding Capability

#### 1D Versions

- UPCA, E / EAN 8, 13 / JAN 8, 13
- Add-ons (sub 2 or P2, sub 5 or P5 & C128)
- RSS-14, Expanded, Stacked, Limited
- ISBN / Bookland EAN
- Code 39 (with full ASCII)
- Pharmacode 39
- Code 128
- Code 93
- Interleaved 2 of 5
- Standard 2 of 5
- IATA
- Code 16K
- Code 11
- Codabar/NW7
- UK/Plessey
- MSI/Plessey

#### PDF Models support these additional symbologies:

- RSS Composites
- PDF-417
- Micro-PDF

### Communications

- RS-232
- Keyboard Wedge
- IBM 46XX
- IBM USB
- USB

### Safety & Regulatory

Electrical: Complies to EN60950, CSA60950, UL60950

Emissions: Complies to FCC-A; EN 55022-B; BSMI113438; AS/NZS 3548; VCCI-B, ICES-005

Laser Classification: IEC 60825 Class I LED

Restriction of Hazardous Substances: Complies to EU RoHS



### Datalogic Scanning, Inc.

Toll free: 1 800 695 5700

International: 1 541 683 5700

E-mail us at: scanning@datalogic.com

www.datalogic.com



Copyright © Datalogic Scanning, Inc. 2005-2007. All rights reserved. Protected to the fullest extent under U.S. and international laws. Copying, or altering of this document is prohibited without express written consent from Datalogic Scanning, Inc. - Datalogic Scanning, Inc. of Eugene, Oregon, USA is ISO registered by NQA. • The Datalogic logo is a trademark of Datalogic SpA. • All brand and product names are trademarks of their respective owners. • Additional information concerning this product or other Datalogic products and services can be found at the Datalogic web site: www.datalogic.com. • Product specifications are subject to change without notice.